
## 1501(P) 4:3 PCAP

## Medical Grade Touchscreen Monitor



## Feature:

- + Flat appearance design
- + ABS + PC Plastic shell
- + Front frame against dust and liquids
- + Industrial grade LCD, LED backlight
- + Resolution 1024X768@60Hz
- + 10 point projection capacitive touchscreen
- + Cover plate anti riot and anti fingerprint
- + Video interface: VGA + HDMI
- + Medical IEC 60601 compliant power supply
- + Stable base with adjustable angle
- + Back VESA mounting option
- + Support OS: Windows/Android/Linux
- + 3-Years warranty

## **Optional:**

- No Touch
- Privacy filter
- Touch interface:RS232
- Video interface:Display Port
- ALL-IN-ONE(Windows/Android)





TDS1501(P) Desktop Touchscreen Monitor Specifications	
Model	1501(P)
Color	Black
Diagonal	15"
Aspect Ratio	4:3
Active Area	304.12×228.09(mm)
Dimensions	350X280X52(mm)
Resolution	1024X768@60Hz
Viewing Angle	Horizontal: 89°/89°, Vertical: 89°/89°
Number of Colors	16.2M
Brightness (typical)	LCD Panel: 350 nits,PCAP: 325 nits
Response Time	20ms
Contrast Ratio	1500:1
Touch Technology Input method	PCAP (Projected Capacitive) - 10 Touch
	Anti-fingerprint coating
	Finger, Capacitance pen(Standard)
	Latex gloves touch (pre commissioning required)
Transmittance	≥90%
Surface hardness	7H(Mohs)
Touch Interface	USB2.0
Video Interface	VGA+HDMI
Speakers	TwoX2W internal speakers
Input Voltage	AC:100-240 VAC, 50/60 Hz
Sealability	Touchscreen sealed to bezel
Drop Test	1kg steel ball falls from 1.2m without breaking
Weight (Unpackage)	4.2KG
Shipping Dimensions	520X340X135(mm)
Operating Temperature	0°C to 40°C
Storage Temperature	-20°C to 60°C
Humidity	Operating: 20% to 70%; Storage: 10% to 80%
MTBF	50,000 hours demonstrated
Mounting Options	VESA:75X75(mm),100X100(mm)
Base	Adjustable Angle 0-90 degrees (Optional)
Power Supply	DC:12V3A
	(CCC\CB\UL Medical certified, ESD standard ±15kV air, ±18kV contact)
Warranty	3-years
Agency Approvals	FCC, CE (CLASSB), ROHS
Support OS	Windows/Linux\Android
What's in the Box	1*USB cable,1*HDMI(8K) cable,1*DC cable

